

[54] PRE-SLIT INJECTION SITE

[75] Inventors: Thomas E. Dudar; Steven C. Jepson, both of Palatine; Robert P. Dobbie, Lincolnshire; Peter L. Graham, Gurnee; Michael J. Finley, Park City; Richard A. Rollins, Mundelein, all of Ill.

[73] Assignee: Baxter International Inc., Deerfield, Ill.

[21] Appl. No.: 425,790

[22] Filed: Oct. 23, 1989

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 147,414, Jan. 25, 1988, abandoned.

[51] Int. Cl.⁵ A61M 25/00

[52] U.S. Cl. 604/283

[58] Field of Search 604/239, 240, 241, 242, 604/243, 271, 272, 273, 274, 283, 405, 411, 412, 413, 414, 415, 416, 905, 84, 85, 86

[56] References Cited

U.S. PATENT DOCUMENTS

3,376,866 4/1968 Ogle .
 3,788,369 1/1974 Killinger .
 3,976,073 8/1976 Quick et al. .
 3,995,630 12/1976 van de Veerdonk .
 4,411,662 10/1983 Pearson .
 4,434,822 3/1984 Bellamy et al. .
 4,583,971 4/1986 Bocquet et al. .
 4,607,671 8/1986 Aalto et al. .
 4,610,674 9/1986 Suzuki et al. 604/282
 4,624,667 11/1986 Rutnarak .
 4,675,020 6/1987 McPhee .
 4,759,756 7/1988 Forman et al. .

4,768,568 9/1988 Fournier et al. .
 4,787,429 11/1988 Valentini .
 4,834,149 5/1989 Fournier et al. .
 4,886,495 12/1989 Reynolds .
 4,969,883 11/1990 Gilbert et al. .

FOREIGN PATENT DOCUMENTS

1037428 8/1978 Canada .
 1043744 12/1978 Canada .
 1215945 12/1986 Canada .
 8812460 2/1989 Fed. Rep. of Germany .

Primary Examiner—C. Fred Rosenbaum

Assistant Examiner—William W. Lewis

Attorney, Agent, or Firm—Paul C. Flattery; Amy L. H. Rockwell; Paul E. Schaafsma

[57] ABSTRACT

A pre-slit injection site includes a housing with a flow path therethrough. A first end of the housing carries a pre-slit septum. A second end of the housing carries a coupling component to adapt the site to standard vials. The coupling component, a vial adapter, includes an adapter spike with openings allowing for the drainage of fluid in the vial through the spike and into the injection site. The vial adapter is provided with a skirt housing unit which protects the adapter spike in manufacturing and use. The skirt housing unit also provides features to lockingly engage the adapter with injection site to standard vials, despite dimensional variations in vial closures. Another embodiment of the coupling component is a spike having a barb feature capable of insertion into a standard vial or port and resisting disengagement.

A blunt cannula is usable with the injection site combined with the coupling components.

11 Claims, 11 Drawing Sheets

